T5 ENERGY SAVING LIGHTING FIXTURE SPECIFICATION

	Lamp lantern spec.						Lamp tube spec.				
Spec /Model	Matched lamp tube	Replacing	Volt. (V)	Cur. (A)	Power (w)	Life-time(Hr)	Color Temp. (K)	Power (w)	Dimension (mm/mm)	Luminous flux (Lm)	Life-time (Hr)
T5 serial connecting lighting fixture SL-IS-14W-110	3 wavelength T5 / 14w	T8 / 20w	110	0.0624	12-14	28000	2700 / 6500	14	L549 / Φ16	1250	10000
T5 serial connecting lighting fixture SL-IS-28W-110	3 wavelength T5 / 28w	T8 / 40w	110	0.127-0.310	26-28	28000	2700 / 6500	28	L1149 / Φ16	2700	10000
T5 serial connecting lighting fixture SL-IS-14W-220	3 wavelength T5 / 14w	T8 / 20w	220	0.0624	12-14	28000	2700 / 6500	14	L549 / Φ16	1250	10000
T5 serial connecting lighting fixture SL-IS-28W-220	3 wavelength T5 / 28w	T8 / 40w	220	0.127-0.310	26-28	28000	2700 / 6500	28	L1149 / Φ16	2700	10000

	Lamp lantern spec.						Lamp tube spec.				
Spec /Model	Matched lamp tube	Replacing	Volt. (V)	Cur. (A)	Power (w)	Life-time(Hr)	Color Temp. (K)	Power (w)	Dimension (mm/mm)	Luminous flux (Lm)	Life-time (Hr)
T5 batten lighting fixture SL-BS-14W-110	3 wavelength T5 / 14w	T8 / 20w	110	0.0624	12-14	28000	2700 / 6500	14	L549 / Φ16	1250	10000
T5 batten lighting fixture SL-BS-28W-110	3 wavelength T5 / 28w	T8 / 40w	110	0.127-0.310	26-28	28000	2700 / 6500	28	L1149 / Φ16	2700	10000
T5 batten lighting fixture SL-BS-14W-220	3 wavelength T5 / 14w	T8 / 20w	220	0.0624	12-14	28000	2700 / 6500	14	L549 / Φ16	1250	10000
T5 batten lighting fixture SL-BS-28W-220	3 wavelength T5 / 28w	T8 / 40w	220	0.127-0.310	26-28	28000	2700 / 6500	28	L1149 / Φ16	2700	10000
T5 batten lighting fixture SL-BS-18W-110	3 wavelength T5 / 18w										
T5 batten lighting fixture SL-BS-18W-220	3 wavelength T5 / 18w										